



MATRIKX® + 1

Extruded Activated Carbon Block Filter

- 0.6 µm Nominal Filtration
- High Chemical Adsorptive Capacity
- High VOC Reduction
- Performance Tested and Verified by Independent Laboratory Testing



MATRIKX® +1 provides comprehensive control of chlorine, taste and odour. MATRIKX® +1 offers: 0.6 µm nominal filtration with extended life as a fine sediment and silt control filter, comprehensive removal of chlorine and chemicals that contribute to taste and odour, and high VOC reduction capacity. The service life of MATRIKX® +1 filters is greatly extended by a prefiltration medium. The MATRIKX® +1 is ideal for use in residential and commercial water purification systems, industrial effluent water treatment, food service, industrial makeup, product rinse, process water, and pre- and post-RO systems which require nearly absolute chlorine reduction.

Technical Specifications and Order Information

Part No.	O.D. x Length	Weight	Chlorine Capacity @ Flow	Nominal µm Rating	Chloroform Reduction	Initial ³ P @ Flow
01-250-125-975	2.50" x 9.75"	0.75 lbs	> 75708 L @ 3.7 Lpm	0.6 µm	2839 L @ 1.8 Lpm	3.5 psid @ 2.75 Lpm
01-250-125-20	2.50" x 20"	1.75 lbs	> 170343 L @ 8.7 Lpm	0.6 µm	6628 L @ 4.5 Lpm	3.0 psid @ 7.5 Lpm
01-250-125-975	4.25" x 9.75"	2.60 lbs	> 264978 L @ 11.3 Lpm	0.6 µm	9842 L @ 5.6 Lpm	9.0 psid @ 7.5 Lpm
01-250-125-20	4.25" x 20"	5.60 lbs	> 567810 L @ 26.5 Lpm	0.6 µm	21198 L @ 13.2 Lpm	8.5 psid @ 15 Lpm



ORDER INFORMATION

Special order filters are available in varying sizes with lengths from 1" to 60".

Standard filters are finished with a prefiltration medium. A protective polypropylene netting is applied to the exterior of the cartridge. Polypropylene end caps with compression gaskets fit most standard housings.

Inquire concerning alternative filter finishing options, including alternative end cap and housing interface styles, a wide range of non-standard extruded filter sizes, and non-standard prefiltration systems.

EXTRUDED CARBON = EXCEPTIONAL VALUE

MATRIKX® + 1 filters consist of activated carbon particles fused into a uniform block with enhanced adsorptive capacity and efficiency. MATRIKX® + 1 filters flow in a radial (outside-to-inside) direction, providing increased dirt-holding capacity and low pressure drop. Unlike granular activated carbon (GAC) filters, MATRIKX® + 1 cartridges will not channel or bypass due to the extreme uniformity of their extruded activated carbon core. Service life of the MATRIKX® + 1 filter is greatly extended by a prefiltration medium.

- No channeling
- No fluidizing
- No bypassing
- Eliminates release of carbon fines
- Lowest extractables, pure materials of construction
- Maximum service life and resistance to fouling
- Graded density prefiltration design
- Manufactured using FDA-compliant materials

Made in the USA.

Distributed by:



FLOWTECH Fluid Handling



FLOWTECH FLUID HANDLING LTD

Gresham Way, READING,
Berkshire, RG30 6AW

Tel: 0118 9413121

Email: filtration@flowtechfh.com

www.flowtechfh.com

LIMITED LIABILITY

KX Industries, L.P. makes no warranties of any kind, expressed or implied, statutory or otherwise, and expressly disclaims all warranties of every kind, concerning the product, including warranties of merchantability or fitness for a particular purpose, except that this product should be capable of performing as described in each product's data sheet. KX Industries, L.P.'s obligation shall be limited solely to the refund of the purchase price or replacement of the product proven defective, at KX Industries, L.P.'s sole discretion. Determination of suitability of the product for uses and applications contemplated by Buyer shall be the sole responsibility of Buyer. Use of this product constitutes Buyer's acceptance of this Limited Liability.

269 South Lambert Road
Orange, CT 06477-3502
Telephone: 203-799-9000

Fax: 203-799-7000

Toll Free: 800-462-8745

E-mail: sales@kxindustries.com
www.kxindustries.com



NOTES

1. Performance of a given MATRIKX® extruded carbon filter varies in direct proportion to the total weight of carbon in each filter. For example, a 4.25" O.D. x 20" L MATRIKX® filter contains approximately seven times as much activated carbon as a 2.50" O.D. x 9.75" L MATRIKX® filter, and will therefore have seven times the rated chlorine capacity when operated at seven times the rated flow of the smaller cartridge. Hence, rated flow is based on maintaining identical contact/residence times for all filters.
2. Chlorine capacity is the estimated capacity in gallons during which the filter will remove >95% of influent free available chlorine (2 ppm) when operating at a given flow and has been tested using the NSF Standard 42 protocol for chlorine reduction.
3. Nominal particulate rating (0.6 µm) is for >85% of a given size as determined from single-pass particle counting results.*
4. Absolute particulate rating (2 µm) is for >99.9% of particles of a given size as determined from single-pass particle counting results.**

* Nominal Filter Rating: Filter rating indicating the approximate size particle, the majority of which will not pass through the filter. It is generally interpreted as meaning that 85% of the particles of the size equal to the nominal micron rating will be retained by the filter. (WQA Glossary of Terms, Third Edition, 3-97).

** Absolute Filter Rating: Filter rating meaning that 99.9% (or essentially all) of the particles larger than a specific micron rating will be trapped on or within the filter. (WQA Glossary of Terms, Third Edition, 3-97).

WARNINGS:

Maximum Operating Temperature:	125°F
Maximum Operating Pressure:	250 psig
Maximum Differential Pressure:	100 psid
Collapse Pressure:	200 psid

MATRIKX® filters are not to be autoclaved or steam-sterilized.

Use MATRIKX® carbon filters only with microbiologically safe and adequately disinfected water. Activated carbon filters are not designed to kill or remove bacteria or viruses.

Actual results obtained will vary with various combinations of organic contaminants, changes in pH or other conditions encountered in actual use.

All information presented here is based on data believed to be reliable. It is offered for evaluation and verification, but is not to be considered a warranty of any kind.

MATRIKX® filters are designed to fit most standard household and commercial or industrial housings.

Contact KX Industries to check filter housing compatibility.

This cartridge must be placed in an appropriate housing and flushed for a minimum of 5 minutes prior to use. Use only with microbiologically safe and adequately disinfected water.

This product is covered by one or more of the following United States Patent Nos. 5,019,311; 5,147,722; 5,189,092; 5,249,948; 5,331,037; 5,685,981; 5,922,803; 5,946,342; 6,061,384; 6,395,190; applicable foreign equivalents; and patents pending.

©2004 KX Industries, L.P. All rights reserved. KX, the KX logo, MATRIKX, and the MATRIKX GENUINE EXTRUDED CARBON seal, are registered trademarks of KX Industries, L.P.